


Product Summary



V_{DS}	$R_{DS(ON_TYP)}$	I_{D_MAX}
-100 V	30 m Ω @ $V_{GS} = -10V$	-30 A
	36 m Ω @ $V_{GS} = -4.5V$	

TO252-3L


Top View



Bottom View


 PIN Configuration
(Top View)


Schematic Diagram

Features

- Low On-Resistance
- Excellent FoM (figure of merit)
- 100% ΔV_{DS} & UIS & R_g tested


Applications

- Load switch
- Motor control
- Switching application

Mechanical Data

- Green molding compound
- Moisture sensitivity: level 1 per J-STD-020
- UL flammability classification rating 94V-0

Ordering Information

Orderable Part Number	Package Type	Device Marking	Form	Quantity (pcs)
SMP10T40ALU	TO252-3L	P10T40AL	13" Tape&Reel	2,500

Maximum Ratings (@ $T_C = 25^\circ\text{C}$, unless otherwise specified.)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	-100	V
Gate - Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($V_{GS} = -10V$) ⁽¹⁾	I_D	$T_C = 25^\circ\text{C}$ -30	A
		$T_C = 100^\circ\text{C}$ -19	A
Pulsed Drain Current ⁽²⁾	I_{DM}	-121	A
Single Pulse Avalanche Energy ⁽³⁾	E_{AS}	160	mJ
Single Pulse Avalanche Current ($L = 0.1\text{mH}$)	I_{AS}	-35	A
Power Dissipation	P_D	$T_C = 25^\circ\text{C}$ 69	W
		$T_C = 100^\circ\text{C}$ 28	W
Junction & Storage Temperature Range	T_J, T_{STG}	-55 ~ +150	$^\circ\text{C}$

Thermal Characteristics







Parameter	Symbol	Typ.	Max.	Unit
Thermal Resistance, Junction-to-Ambient ⁽⁴⁾	$R_{\theta JA}$	30	38	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Case ⁽⁵⁾	$R_{\theta JC}$	1.4	1.8	$^\circ\text{C/W}$







Electrical Characteristics (@ $T_J = 25^\circ\text{C}$, unless otherwise specified.)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Off Characteristics ⁽⁶⁾						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-100	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -100V, V _{GS} = 0V	-	-	-1.0	μA
		T _J = 125°C	-	-	-100	μA
Gate-Source Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics ⁽⁶⁾						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D = -250μA	-1.2	-1.8	-2.5	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = -10V, I _D = -15A	-	30	40	mΩ
		V _{GS} = -4.5V, I _D = -10A	-	36	50	mΩ
Forward Transconductance	g _{fs}	V _{DS} = -5.0V, I _D = -15A	-	30	-	S
Diodes Forward Voltage	V _{SD}	I _S = -2.0A, V _{GS} = 0V	-	-0.7	-1.2	V
Dynamic Characteristics ⁽⁷⁾						
Input Capacitance	C _{iss}	V _{DS} = -50V, V _{GS} = 0V, f = 1MHz	-	1402	-	pF
Output Capacitance	C _{oss}		-	317	-	pF
Reverse Transfer Capacitance	C _{rss}		-	14	-	pF
Gate Resistance	R _g	V _{GS} = 0V, V _{DS} = 0V, f = 1MHz	-	5.4	-	Ω
Switching Characteristics ⁽⁷⁾						
Turn-On DelayTime	t _{d(on)}	V _{GS} = -10V, V _{DS} = -50V I _D = -15A, R _{GEN} = 3.0Ω	-	5.7	-	ns
Rise Time	t _r		-	14	-	ns
Turn-Off DelayTime	t _{d(off)}		-	28	-	ns
Fall Time	t _f		-	26	-	ns
Gate Charge Characteristics ⁽⁷⁾						
Total Gate Charge (V _{GS} = -10V)	Q _g	V _{DS} = -50V, I _D = -15A V _{GS} = -10V	-	23	-	nC
Total Gate Charge (V _{GS} = -4.5V)	Q _g		-	11	-	nC
Gate-Source Charge	Q _{gs}		-	4.9	-	nC
Gate-Drain Charge	Q _{gd}		-	4.2	-	nC
Gate Plateau Voltage	V _{plateau}		-	-3.7	-	V
Drain-Source Diode Characteristics ⁽⁷⁾						
Body Diode Reverse Recovery Time	t _{rr}	I _F = -15A, dI/dt = 100A/μs, T _J = 25°C	-	53	-	ns
Body Diode Reverse Recovery Charge	Q _{rr}		-	103	-	nC
Diode Forward Current	I _S	T _C = 25°C	-	-	-30	A


Notes:

1. This current is chip limited, which is calculated based on R_{thjc} .
2. This current is calculated on single pulse with 10 μs Single Pulse.
3. Defined by design, not subject to production test, E_{AS} condition: $T_J=25^\circ\text{C}, V_{DD}=-50V, V_{GS}=-10V, L=1.0\text{mH}$.
4. Device mounted on FR-4 substrate PC board with 2oz copper in 1inch square cooling area.
5. Thermal resistance from junction to the exposed pad.
6. Short duration pulse test used to minimize self-heating effect.
7. Defined by design, not subject to production.

Typical Electrical and Thermal Characteristics

Figure 1: Output Characteristics

Figure 2: Transfer Characteristics

Figure 3: On-Resistance vs. Gate-Source Voltage

Figure 4: On-Resistance vs. Drain Current and Gate Voltage

Figure 5: On-Resistance vs. Junction Temperature

Figure 6: Source-Drain Diode Forward Voltage

Typical Electrical and Thermal Characteristics

Figure 7: Gate Threshold Variation vs. Junction Temperature

Figure 8: Gate Charge Characteristics

Figure 9: Capacitance Characteristics

Figure 10: Power Derating

Figure 11: Current Derating

Figure 12: Safe Operating Area

Typical Electrical and Thermal Characteristics

Figure 13: Normalized Maximum Transient Thermal Impedance

TO252-3L Package Outline
Package Outline

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M,1994.
2. ALL DIMNESIONS IN MILLIMETER (ANNGLE IN DEGREE).
3. DIMENSIONS "D" AND "E1" DO NOT INCLUDE MOLD FLASH PROTRUSIONS OR GATE BURRS.

DIM.	MILLIMETER		
	MIN.	NOM.	MAX.
A	2.20	2.30	2.40
A1	0	-	0.13
b	0.62	0.76	0.90
c	0.40	0.50	0.61
c1	0.46	0.50	0.58
D	5.90	6.10	6.30
D1	5.05	--	--
E	6.35	6.60	6.80
E1	4.32	--	--
b3	5.21	5.38	5.55
e	2.29 BSC		
H	9.40	10.00	10.40
L	0.89	--	1.27
L2	1.40	--	1.78
V1	7° REF		
V2	0°	-	6°

Recommend Soldering Footprint
