Product Summary

V_{DS}	$R_{DS(ON)_TYP}$			I_{D_MAX}
100 V	5.4 mΩ	@V_{GS} = 10V	TO263-3L	110 A
	5.7 mΩ	@V_{GS} = 10V	TO220-3L	

Features

- Low On-Resistance
- Excellent FoM (figure of merit)
- 100% ΔVDS & UIS & Rg Tested

RoHS HALOGEN FREE

TO220-3L



Top View

TO263-3L

Top View



PIN Configuration
(Top View)



Schematic Diagram

Applications

- Motor controls
- DC/DC in Telecoms and Inductrial
- High frequency switching, synchronous rectification

Mechanical Data

- Green Molding Compound
- Moisture Sensitivity: Level 1 per J-STD-020
- UL Flammability Classification Rating 94V-0

Ordering Information

Orderable Part Number	Package Type	Device Marking	Form	Quantity (pcs)
SMT10T06AHS	TO220-3L	10T06AH	Tube	50
SMT10T06AHT	TO263-3L	10T06AH	13" Tape&Reel	1,000

Maximum Ratings (@ T_C = 25°C, unless otherwise specified.)

Parameter		Symbol	Value	Unit
Drain - Source Voltage		V_{DS}	100	V
Gate - Source Voltage		V_{GS}	±20	V
Continuous Drain Current (V_{GS} = 10V) (1)	T_C = 25°C	I_D	110	A
	T_C = 100°C		77	A
Pulsed Drain Current (2)		I_{DM}	438	A
Single Pulse Avalanche Energy (3)		E_{AS}	384	mJ
Single Pulse Avalanche Current (L= 0.1mH)		I_{AS}	50	A
Power Dissipation	T_C = 25°C	P_D	158	W
	T_C = 100°C		79	W
Junction & Storage Temperature Range		T_J, T_{STG}	-55 ~ +175	°C

Thermal Characteristics

Parameter	Symbol	Typ.	Max.	Unit
Thermal Resistance, Junction-to-Ambient (4)	$R_{\theta JA}$	36	45	°C/W
Thermal Resistance, Junction-to-Case (5)	$R_{\theta JC}$	0.73	0.95	°C/W

Electrical Characteristics (@ T_J = 25°C, unless otherwise specified.)

Parameter	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Off Characteristics [6]							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA		100	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 100V, V_{GS} = 0V		-	-	1.0	μA
			T_J = 125°C	-	-	100	μA
Gate-Source Leakage Current	I_{GSS}	V_{GS} = ±20V, V_{DS} = 0V		-	-	±100	nA
On Characteristics [6]							
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS} = V_{DS}, I_D = 250μA		2.0	3.0	4.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS} = 10V, I_D = 20A	TO263-3L	-	5.4	6.5	mΩ
			TO220-3L	-	5.7	6.8	mΩ
Forward Transconductance	g_{fs}	V_{DS} = 5.0V, I_D = 20A		-	24	-	S
Diodes Forward Voltage	V_{SD}	I_S = 2.0A, V_{GS} = 0V		-	0.7	1.2	V
Dynamic Characteristics [7]							
Input Capacitance	C_{iss}	V_{DS} = 50V, V_{GS} = 0V, f = 1MHz		-	2472	-	pF
Output Capacitance	C_{oss}			-	978	-	pF
Reverse Transfer Capacitance	C_{rss}			-	15	-	pF
Gate Resistance	R_g	V_{GS} = 0V, V_{DS} = 0V, f = 1MHz		-	1.1	-	Ω
Switching Characteristics [7]							
Turn-On DelayTime	$t_{d(on)}$	V_{GS} = 10V, V_{DS} = 50V I_D = 20A, R_{GEN} = 3.0Ω		-	6.5	-	ns
Rise Time	t_r			-	9.5	-	ns
Turn-Off DelayTime	$t_{d(off)}$			-	34	-	ns
Fall Time	t_f			-	23	-	ns
Gate Charge Characteristics [7]							
Total Gate Charge (V_{GS} = 10V)	Q_g	V_{DS} = 50V, I_D = 20A V_{GS} = 10V		-	38	-	nC
Total Gate Charge (V_{GS} = 6.0V)	Q_g			-	21	-	nC
Gate-Source Charge	Q_{gs}			-	6.4	-	nC
Gate-Drain Charge	Q_{gd}			-	8.5	-	nC
Gate Plateau Voltage	$V_{plateau}$			-	4.7	-	V
Drain-Source Diode Characteristics [7]							
Body Diode Reverse Recovery Time	t_{rr}	I_F = 20A, dI/dt = 100A/μs, T_J = 25°C		-	58	-	ns
Body Diode Reverse Recovery Charge	Q_{rr}			-	115	-	nC
Diode Forward Current	I_S	T_C = 25°C		-	-	110	A

Notes:

1. This current is chip limited, which is calculated based on Rthjc.
2. This current is calculated on single pulse with 10us Single Pulse.
3. Defined by design, not subject to production test, E_{AS} condition: T_J=25°C, V_{DD}=50V, V_{GS}=10V, L=1.0mH.
4. Device mounted on FR-4 substrate PC board with 2oz copper in 1inch square cooling area.
5. Thermal resistance from junction to the exposed pad.
6. Short duration pulse test used to minimize self-heating effect.
7. Defined by design, not subject to production.

Typical Electrical and Thermal Characteristics



Figure 1: Output Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Gate-Source Voltage



Figure 4: On-Resistance vs. Drain Current and Gate Voltage



Figure 5: On-Resistance vs. Junction Temperature



Figure 6: Source-Drain Diode Forward Voltage

Typical Electrical and Thermal Characteristics



Figure 7: Gate Threshold Variation vs. Junction Temperature



Figure 8: Gate Charge Characteristics



Figure 9: Capacitance Characteristics



Figure 10: Power Derating



Figure 11: Current Derating



Figure 12: Safe Operating Area

Typical Electrical and Thermal Characteristics



Figure 13: Normalized Maximum Transient Thermal Impedance

TO220-3L Package Outline

Package Outline



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
2. ALL DIMNESIONS IN MILLIMETER (ANNGLE IN DEGREE).
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH.

DIM.	MILLIMETER		
	MIN.	NOM.	MAX.
A	4.35	4.50	4.70
A1	2.20	2.30	3.00
b	0.70	0.80	0.95
b1	1.10	1.30	1.50
C	0.45	0.50	0.60
C1	1.23	1.30	1.40
H	28.00	28.80	29.80
D	8.80	9.21	9.90
D1	12.80	13.20	13.60
E	9.70	10.00	10.50
E1	7.40	8.00	8.60
L	--	--	3.80
L1	6.25	6.50	6.90
L2	2.40	2.90	3.05
e	2.54 BSC		

TO263-3L Package Outline

Package Outline



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
2. ALL DIMNESIONS IN MILLIMETER (ANNGLE IN DEGREE).
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH.

DIM.	MILLIMETER		
	MIN.	NOM.	MAX.
A	4.20	4.50	4.70
A1	2.30	--	2.85
A2	0.00	0.10	0.25
b	0.70	0.80	0.95
b1	1.15	1.30	1.70
C	0.30	0.50	0.60
C1	1.15	1.30	1.42
H	14.00	15.20	15.88
D	8.50	9.20	9.60
D1	7.50	7.75	8.00
E	9.78	10.00	10.36
E1	7.60	7.95	8.10
L	1.50	--	2.50
L1	--	--	1.75
e	--	2.54	--

Recommended Footprint (Dimensions are in mm)

Recommended Soldering Footprint :



DIMENSIONS IN MILLIMETERS